

Flame Retardant

BCH FR & FR-LSH Wires



BCH ELECTRIC LIMITED

1105, New Delhi House, 27, Barakhamba road, New delhi - 110001 Ph. :91-11-23316029/3610/6539/43673100,
Email : marketing@bchindia.com

Price List No : BCH/WNC/FLEX/SC_NR/100 M/L.P/2021-22/2B W.E.F Dated -01.05.2021

SINGLE CORE PVC CABLES (Unsheathed)

BCH PVC INSULATED FLEXIBLE COPPER CONDUCTOR UNSHEATHED SINGLE CORE INDUSTRIAL(MULTISTRAND) CABLES WITH BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V, AS PER IS 694/2010

SIZE Sq.m	1core Pvc Cables		Single Core FR PVC Cables				Single Core FR-LSH PVC Cables			
	100 Mtr. Coil	Coils Per Box	90 Mtr. Coil	Coils Per Box	100 Mtr. Coil	180 Mtr. Coil	90 Mtr. Coil	Coils Per Box	100 Mtr. Coil	180 Mtr. Coil
0.50	907	20	863	20	-	1726	900	20	-	1800
0.75	1306	18	1185	18	-	2370	1254	18	-	2508
1.00	1686	20	1539	20	-	3078	1628	20	-	3255
1.50	2438	18	2253	18	-	4506	2396	18	-	4792
2.50	3941	10	3596	10	-	7192	3818	10	-	7636
4	6182	5	5605	5	-	11210	5874	5	-	11748
6	9158	5	8348	5	-	16696	8672	5	-	17345
10	15923	-	14511	-	-	-	15019	-	-	-
16	25327	-	-	-	25572	-	-	-	26538	-
25	40661	-	-	-	40937	-	-	-	42411	-
35	56877	-	-	-	57261	-	-	-	59324	-
50	80340	-	-	-	-	-	-	-	-	-
70	114950	-	-	-	-	-	-	-	-	-
95	153917	-	-	-	-	-	-	-	-	-
120	199155	-	-	-	-	-	-	-	-	-
150	246878	-	-	-	-	-	-	-	-	-
185	303164	-	-	-	-	-	-	-	-	-

3 CORE SUBMERSIBLE FLAT CABLES

BCH 3CORE FLAT PVC CABLES WITH BRIGHT ANNEALED BARE COPPER CONDUCTOR, RoHS PVC/XLPE INSULATION & PVC SHEATH FOR SUBMERSIBLE PUMP MOTORS, SUITABLE FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS 694/2010

SIZE (Sq.m)	No Of Core	Submersible Cable PVC Insulated			Submersible Cable THICK			Submersible Cable XLPE		
		RS/Mtr.	RS/100 Mtr.	RS/500 Mtr.	RS/Mtr.	RS/100 Mtr.	RS/500 Mtr.	RS/Mtr.	RS/100 Mtr.	RS/500 Mtr.
1.00	3 Core	74.46	7,446	37230	79.60	7,960	39798	-	-	-
1.50	3 Core	87.79	8,779	43893	92.43	9,243	46217	96.29	9,629	48143
2.50	3 Core	138.15	13,815	69077	145.07	14,507	72535	152.77	15,277	76386
4	3 Core	204.51	20,451	102253	214.39	21,439	107197	221.46	22,146	110728
6	3 Core	302.49	30,249	151244	308.11	30,811	154056	321.59	32,159	160796
8	3 Core	406.90	40,690	203450	-	-	-	436.49	43,649	218246
10	3 Core	511.50	51,150	255752	536.63	53,663	268314	553.32	55,332	276659
16	3 Core	808.62	80,862	404310	-	-	-	-	-	-
25	3 Core	1270.05	127,005	635024	-	-	-	-	-	-
35	3 Core	1758.81	175,881	879403	-	-	-	-	-	-

MULTI CORE PVC CABLES

BCH MULTISTRAND BRIGHT ELECTROLYTIC ANNEALED BARE COPPER CONDUCTOR, PVC INSULATED & PVC SHEATHED MULTICORE ROUND FLEXIBLE CABLES FOR WORKING VOLTAGES UPTO & INCLUDING 1100 Volts, AS PER IS 694/2010

SIZE (Sq.m)	NO OF CORE				SIZE (Sq.m)	NO OF CORE			
	1 CORE RS/100 M	2 CORE RS/100 M	3 CORE RS/100 M	4 CORE RS/100 M		1 CORE RS/100 M	2 CORE RS/100 M	3 CORE RS/100 M	4 CORE RS/100 M
0.50	907	2793	3,650	4,669	6	9158	21,931	30,523	40031
0.75	1306	3707	4,965	6,345	10	15923	37,135	53,938	70863
1.00	1686	4576	6,202	7,933	16	25327	58,361	83,108	109980
1.50	2438	6037	8,261	10,794	25	40661	93,180	132,099	176554
2.50	3941	9553	13,286	17,376	35	56877	-	185,352	247982
4	6182	14876	20,495	26,976	-	-	-	-	-

BCH MULTISTRAND BRIGHT ELECTROLYTIC ANNEALED BARE COPPER CONDUCTOR, PVC INSULATED & PVC SHEATHED MULTICORE ROUND FLEXIBLE CONTROL CABLES FOR WORKING VOLTAGES UPTO & INCLUDING 1100 Volts, AS PER IS 694/2010

SIZE (Sq.m)	NO OF CORE									
	5 CORE RS/100 M	6 CORE RS/100 M	7 CORE RS/100 M	8 CORE RS/100 M	10 CORE RS/100 M	12 CORE RS/100 M	14 CORE RS/100 M	16 CORE RS/100 M	19 CORE RS/100 M	24 CORE RS/100 M
0.50	6,165	6,952	7,899	9,378	11,636	13,666	15,831	17,930	21,157	27,081
0.75	8,409	10,062	11,171	13,393	16,378	19,480	22,622	26,057	31,417	39,352
1.00	10,685	12,283	13,989	16,662	20,565	24,639	28,311	32,356	39,894	49,098
1.50	14,516	17,570	20,097	23,345	29,232	34,836	40,557	45,683	54,052	69,256
2.50	23,473	28,598	32,766	37,995	47,873	56,390	65,506	75,596	89,051	112,866